

Specifications

- Rotation speed 20 to 100 rpm.
- Pneumatic pressure is electronically adjustable.
- Time display.
- Pressure display.
- Control LED.
- Motoreducer power: 90 Watts.
- Voltage: 230 V single.
- Built in accordance with EEC standards.
- Frame in composite material.
- Diluent tank: 150 ml.

POLISHING HEAD PE.RE



Width: 430 mm
Depth: 200 mm
Height: 300 mm
Weight: 25 kg.

Operating

The specimen holder PE.RE enables to polish simultaneously up to 6 specimens \varnothing 50 mm on a plate with central pressure.

The control panel is equipped with touch sensitive keys and shows electrical display of the pressure from 0,5 to 30 daN, electronic display of the time from 10s. to 99 minutes, selection of the diluents and command to program the Distridiam 6.

Accessories

- 57102 - specimen holder \varnothing 160 mm 6 holes from \varnothing 25 to 32
- 57103 - specimen holder \varnothing 160 mm 4 holes from \varnothing 32 to 40
- 57104 - specimen holder \varnothing 160 mm 4 holes from \varnothing 40 to 50
- 57105 - plain plate \varnothing 160 mm
- 57106 - plate Diam 160 mm 6 holes \varnothing 30 with annular clamping
- 57107 - plate \varnothing 160 mm 4 holes \varnothing 40 with annular clamping
- 57119 - plate \varnothing 180 mm 6 holes \varnothing 38 to 50
- 57116 - Hooking system for plate PE.RE.

TECNIMETAL

IGNACIO ELLACURÍA, 10-12
TELS. 91 356 22 94 - FAX: 91 355 58 08
28017 MADRID

38320 Brié et Angonnes - Gr
E-mail : presi@presi.com

E-mail: info@tecnimetal.com